



EVO-STIK THE DOG'S B*LL*CKS

MULTI-PURPOSE ADHESIVE & SEALANT

Date: 18 April 2018

YOUR SMART ADVANTAGES

- Hybrid SMP technology; Multi-Purpose Adhesive & Sealant – eliminates the need for numerous adhesives and sealants.
- High strength adhesive and anti-mould sealant perfect for kitchens and bathrooms
- Weatherproof, waterproof, UV resistant, overpaintable and available in 6 colours including Crystal.

USES

EVO-STIK THE DOG'S B*LL*CKS is specially formulated using hybrid SMP technology and is designed to eliminate the need for numerous adhesives and sealants. EVO-STIK THE DOG'S B*LL*CKS is suitable for bonding a variety of materials used both indoors and outdoors. EVO-STIK THE DOG'S B*LL*CKS can be used for sealing joints with low ability to absorb movement.

PRODUCT CHARACTERISTICS

Colour	White Black Grey Ivory Brown Crystal
Base	Silan-terminated polymers, neutrally cross-linked
Specific Gravity	1.1 at 23°C and 50% relative humidity
Curing Method	Moisture Curing

Product Code	White: 30610662 Black: 30610593 Grey: 30610595 Ivory: 30610596 Brown: 30610688 Crystal: 30610687
--------------	---

Storage/Shelf Life	18 months from the date of manufacture (12 months for Crystal) when stored in the dry between +5°C & +25°C, out of direct sunlight. Protect from frost.
--------------------	---

TYPICAL PERFORMANCE DATA (Approx.)

Application	+5°C to +40°C
Service Temperature	-40°C to +100°C
Coverage	Approx. 14 linear metres of 5mm diameter bead per C20 cartridge
Drying Times	Skin Formation: 15 minutes dependent on temperature & humidity. Through Dry: Approx. 2mm per 24 hours and 50% relative humidity. Always tool sealant within 20 minutes of application.
Movement Capability	15 %, relative to the initial width of the joint
Elongation	approx. 250%

DIRECTIONS FOR USE

Before using EVO-STIK THE DOG'S B*LL*CKS refer to the relevant Health & Safety Data Sheet. Available at www.bostik.com/uk named as the code above.

PREPARATION

1. Joint surfaces must be clean, sound and free from dust and other contaminants that may impair adhesion.
2. If desired place masking tape along the joint edges before application. This can make it easier to make a neat, tooled finish. Use a spatula with a round end to tool the sealant and check that this tool just fits into the gap between the masking tape so that it catches the excess sealant.
3. Do a test run without applying any sealant to 'get a feel' for the difficult areas to seal in corners, behind taps and raised joints.

APPLICATION

1. Unscrew the nozzle, and using a sharp knife, cut off the dome of the cartridge, taking care not to damage the thread. Screw the nozzle onto the cartridge.
2. Cut off the tapered end of the nozzle at a 45° angle, to a width matching the gap to be sealed.
3. Fit the cartridge into the cartridge gun by pressing the release plate and pulling out the plunger. Insert cartridge and repeatedly squeeze the trigger until the sealant appears.
4. Place the nozzle at the start of the gap, and gently squeeze the trigger. Push forward slowly, ensuring that contact is made by the sealant with both sides of the gap. At the end of the run, release the trigger and press the plunger release plate of the gun.
5. Smooth the sealant with a wet, round ended tool (do not use a wetted finger), remove any excess with a cloth moistened with white spirit and then remove the masking tape from either side of the bead.
6. The sealant skins over rapidly (approx. 15 minutes) and is fully cured in approx. 1-2 days depending on bead width, temperature and humidity.

CLEANING

1. **Uncured Sealant.**
The bulk should be removed carefully using a soft scraper. The remainder can be removed using a cloth just moistened with white spirit. Repeat using another clean cloth moistened with white spirit.
2. **Cured sealant**
There is no adequate solvent; carefully cut away excess with a very sharp knife. Do not use solvent to remove product from skin – use soap and water.
3. For the sealant to continue to work effectively, ensure that it is cleaned regularly and not submerged under water.

PRECAUTIONS IN USE

EVO-STIK THE DOG'S B*LL*CKS cannot be applied to surfaces which have frost or ice on them. Do not use on polyolefines

(eg. PE, PP), polyhalogenolefines (eg. Teflon™) and similar plastics. Will not resist abrasion in floor joints. Do not use in swimming pools. Do not use for aquarium applications. Prevent entry of uncured sealant into drains or watercourses. Do not use on or against bitumen. Not suitable for bedding double glazed/insulating glass units into frames. Do not submerge under water.

For any application not covered please contact technical services on +44 (0) 1785 272625 or visit www.bostik.com/uk for advice

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK THE DOG'S B*LL*CKS.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



